

SwimCross™ Exercise Systems | X200



Imagine a day that begins with your wellness in mind.

A sunrise swim or rigorous aquatic workout clears your mind and leaves you with a sense that there are unlimited opportunities for the day ahead. This day is made possible by the SwimCross™ exercise system, from the makers of Endless Pools®. The X200 blends the functionality of swimming and exercising in the privacy of your home with a uniquely beautiful design that puts the SwimCross exercise system in a class of its own.

From the makers of



X200

SwimCross™ Exercise Systems



Dimensions (L x W x H)	366 x 226 x 127 cm
Water Capacity	4,575 litres
Weight	1,025 (Dry) / 6,400kg (Filled*)
Shell Colour Options	Alpine White or Ice Grey
Cabinet Colour Options	Dark Mocha or Grey Oak
Swim Technology	5 Swim Jets – Max 1,200 litres Per Minute
Swim Jet Pumps	2.5 HP Continuous Duty; 5.2 HP Breakdown Torque – 1 Single Speed & 1 Dual Speed
Hydromassage Seats	3
Hydromassage Jets - 27	1 Large Jet, 2 Rotary Jets, 2 Directional Jets, 22 Mini Jets
Hydromassage Jet Pump	2.5 HP Continuous Duty; 5.2 HP Breakdown Torque – Dual Speed Pump
Control System**	LCD Control Panel; 220 - 240V, 2 x 24A, 50Hz
Water Feature	Illuminated Waterfall
Water Management System	UVC + CD Ozone
Effective Filtration Area	9m ²
Lighting System	Multi-Colour 15 LED Lights & 13 cm Main Light
Substructure	2 mm Galvanised Steel Frame
Base Pan	Thermoformed ABS Base Pan
Heater	3000 watt
Energy Efficiency	Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California Law
Stainless Steel Grab Rails	3 Satin Stainless Steel Rails
Music Option	8 Speakers + Subwoofer, Bluetooth® Enabled
Exercise Equipment Options	Swim Tether and Rowing Kit
Vinyl Cover & Lifter Options	Watkins Bi-Fold Covers & Lifters or VacuSeal™ Cover System
Additional Options	Floor Mirror, Gecko® In.Touch Wi-Fi & Mobile App

Shell Colours



Ice Grey



Alpine White

Cabinet Colours



Grey Oak



Dark Mocha

*Includes water and 10 adults weighing 80 kg each
**Also offered in a 3 Phase configuration 380-415V, 3N~, 16A, 50Hz, Three Phase 16A/phase G.F.C.I protected circuit, other electrical configurations possible

All rights reserved. Specifications, colours, and surface materials subject to change without notice

